

FOLDING ROOFS, HIGH POWER HIFI, AUTO TAILGATE DEMOS

The new **SSU2-50/S** provides a stable voltage and up to 50 amps of fully regulated power to prevent loss of charge and damage to the battery without any fan noise ensuring a noise free environment for your sales customers.

SSU2-50/S can be used with any 12V automotive battery including AGM and GEL.

When the battery is charged the SSU is a regulated power supply to sustain accessory loads and offset parasitic drain.

Battery state detection, ensuring safe prolonged use.

Output current display.

Reverse polarity protection.

Disconnect detection.

Supplied with 5M IEC power lead and 5M output leads.

Silent operation

FEATURES

SSU2

50/S

This low profile (90mm) battery conditioner has been designed specifically for car showrooms.

Most conventional battery conditioners simply trickle charge the battery after it has been drained. The **SSU2-50/S** provides instant support to the battery negating the need for recharging.

With the **SSU2-50/S** showroom conditioner connected to your vehicles you can be sure that they are always ready for demonstration and that the battery will be kept in prime condition.

This unit has been designed to slip under most vehicles without scratching the floor surface and features automatic current

sensing so that it knows when it is needed.

The intelligent sensing in the **SSU2-50/S** determines exactly when support is required to minimize unnecessary noise and power consumption.



SPECIFICATIONS

INPUT

100-240VAC

50/60Hz

OUTPUT

13.4v UP TO 50A

CONTINUOUS

WEIGHT

13.2LB

SIZE

11" x 7.5" x 3.5"

FORMAT

US MAINS INPUT LEAD VARIANT

CARTON

15.7" x 15.7" x 7.8"

SHOWROOM SUPPORT UNIT

CALL: 610-605-3634

US.SALES@TRACTION-DIRECT.COM

TRACTION-DIRECT.COM